RE Li³ ON®

LITHIUM IRON PHOSPHATE SAFETY DATA SHEET (SDS)



SECTION 1 - COMPANY AND PRODUCT IDENTIFICATION

Product Name: Lithium Iron Phosphate Rechargeable Battery Common Name: Lithium Iron Phosphate Battery LiFePO4) Product Use: Electric Storage Battery Distributed By: RELiON Battery, LLC Address: 4868 Harrisburg Rd, Fort Mill, SC 29707 USA Phone Number: 803-547-3522 Fax Number: 803-547-3526 Email: powerpros@relionbattery.com Emergency Number: 803-547-3522 Revision Date: December 19, 2017

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview: This product contains a chemical substance. Safety information is given for exposure to the product as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture, the below hazards exist.

CAS# 1333-86-4 Classification According to GHS

Self-heating substances and mixtures (1) Carcinogenicity (2) Specific target organ toxicity, repeated exposure (1) (lung)

Label Elements Hazard Images:



Signal Word: Danger Hazard Statements: H251 Self-heating; may catch fire H351 Suspected of causing cancer H372 Causes damage to organs through prolonged or repeated exposure (lung) **Precautionary Statements: Prevention:** P235 Keep cool. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves, protective clothing, eye protection and face protection. P260 Do not breathe dust. P264 Wash skin and clothing thoroughly after handling. P270 Do not eat, drink or smoke when using this product. **Response:** P308 + P313 If exposed seek medical attention. P314 Seek medical attention if you feel unwell. Storage: P407 Maintain air gap between stacks or pallets. P413 Store bulk masses greater than ...kg/...lbs at temperatures not exceeding ...C P420 Store separately. P405 Store locked up. Disposal: P501 Contents require disposal at approved waste treatment plants.

CAS# 7440-50-8

Classification according to GHS

Sensitisation skin (1, 1A, 1B)

Specific target organ toxicity, single exposure (1) (digestive system) Specific target organ toxicity, single exposure; Respiratory tract irritation (30

Label Elements Hazard Images:



Signal word: Danger Hazard Statements: H317 May cause allergic skin reaction. H370 Causes damage to organs (digestive system). H335 May cause respiratory irritation.

relionbattery.com

+1.803.547.7288 844.385.9840

© 2017 Relion Battery, LLC. All rights reserved. Relion Battery is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Relion Battery reserves the right to make adjustments to this publication at any time, without notice or obligatior

9868 Harrisburg Road Fort Mill, SC 29707, US





Prevention:

P260 Do not breathe dust, fume.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, eye protection, face protection.P264 Wash skin and clothing thoroughly after handling.P270 Do not eat, drink or smoke when using this product.P271 Use only outdoors or in a well-ventilated area.

Response:

P302+P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Seek medical attention.
P321 Specific treatment (See additional emergency instructions).
P362 + P364 Take off contaminated clothing and wash it before reuse
P308 + P311 IF exposed or concerned: Call a POISION CONTROL CENTER.
P312 Call a POISION CENTER if you feel unwell.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Contents handling to approved waste treatments.

CAS# 7429-90-5

Classification according to GHS

Substances and mixtures which, in contact with water, emit flammable gases (2, 3)

Specific target organ toxicity, repeated exposure (1) (Lung) Hazardous to the aquatic environment, long-term hazard (4)

Label Elements Hazard Images:



Signal word: Danger

Hazard Statements:

H261 In contact with water releases flammable gas. H372 Causes damage to organs through prolonged or repeated. exposure (Lung).

H413 May cause long lasting harmful effects to aquatic life.

Prevention:

P223 Do not allow contact with water.

P231 + P232 Handle and store contents under inert gas, protect with moisture.

P280 Wear protective gloves and clothing thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P273 Avoid release to the environment.

P273 Avoid release to the environment

Response:

P302 + P335 + P334 IF ON SKIN: Brush off loose particles from skin and immerse in cool water.

 $\mathsf{P370} _ \mathsf{P378}$ In case of fire: use the appropriate media to put out the fire.

P314 Seek medical attention if you feel unwell.

Storage:

P402 + P404 Store in a dry place. Store in a closed container. **Disposal:**

P501 Contents handling to approved waste treatment plants.

Other Hazards

Physical and Chemical hazards: See Section 10 Human Health Hazards: See Section 11 Environmental Hazards: See Section 12

relionbattery.com



© 2017 Relion Battery, LLC. All rights reserved. Relion Battery is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Relion Battery reserves the right to make adjustments to this publication at any time, without notice or obligation

+1.803.547.7288 844.385.9840





SECTION 3 - COMPOSITION/INFORMATION **ON INGREDIENTS**

Chemical Characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Ferrous Phosphate Litium	15365-14-7	476-700-9	38.09
Carbon Black	133-86-4	215-609-9	0.62
Rubber, styrene- butadiene, fume	61789-96-6	612-382-1	0.34
Polyvinylidene fluoride resin	24937-79-9	607-458-6	1.04
Graphite	7782-42-5	231-955-3	20.10
Phosphate (1-), hexafluoro-, lithium	21324-40-3	244-334-7	1.10
Copper	744-50-8	231-159-6	9.22
Aluminium	7429-9-5	231-072-3	4.00

SECTION 4 - FIRST AID MEASURES

Description of First Aid Measures

General Information: No special measures required. After Eve Contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After Skin Contact

Remove contaminated clothing and shoes. Immediately wash with water and soap, rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After Inhalation

Remove victim to non exposed area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After Swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available

Most important symptoms/effects, acute and delayed: No data available

Indication of immediate medical attention and special treatment needs: No data available

SECTION 5 - FIRE FIGHTING MEASURES

Suitable extinguishing media:

Use extinguishing agent suitable for local conditions and the surrounding environment, such as dry powder, CO2. Unsuitable extinguishing media: No data available.

Specific Hazards Arising from the Chemical:

Special hazards arising from the substance or mixture Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolytes that may vent, ignite and spark when subjected to high temperature (>150°C (302°F), when damaged or abused (e.g.) mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

Specific protective actions for fire-fighters:

Protective equipment: wear self-contained respirator. Wear fully protective impervious suit.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Protective Equipment: No data available.

Emergency Procedures: Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust. Collect as much of the spilled material as possible, place the spilled material into a suitable container for disposal. Keep spilled material out of sewers, ditches and bodies of water.

Environmental Precautions: Do not allow material to be released into the environment without proper governmental permits.

Methods and Materials for Containment and Cleaning Up: All waste must refer to the United Nations, the national and local regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.



relionbattery.com

+1.803.547.7288

2017 Relion Battery, LLC. All rights reserved, Relion Battery is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Relion Battery reserves the right to make adjustments to this publication at any time, without notice or obligation

9868 Harrisburg Road 844.385.9840 Fort Mill, SC 29707, US

REL^{i³ON[®]}

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling:

Consumption of food and beverage should be avoided in work areas. Wash hands with soap and water before eating or drinking. Ground containers when transferring liquid to prevent static accumulation and discharge.

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Conditions for safe storage, including any incompatibilities: Requirements to be met by storerooms and receptacles Store in a cool, dry, well-ventilated place.

Information about storage in one common storage facility Keep away from heat, avoiding long exposure to sunlight. Further information about storage conditions Keep container tightly sealed

Specific and use: No data available

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

CAS No.	ACGIH	NIOSH	OSHA
15365-14-7	N/A	N/A	N/A
1333-86-4	TVL-TWA 3mg/m ³	REL-TWA 3.5mg/m ³	PEL-TWA 3.5mg/m ³
61789-96-6	N/A	N/A	N/A
24937-79-9	N/A	N/A	N/A
7782-42-5	TVL-TWA 2mg/m ³	REL-TWA 2.5mg/m ³	PEL-TWA 15mppcf PEL-TWA 20mppcf
21324-40-3	N/A	N/A	N/A
7440-50-8	TVL-TWA 0.2mg/m ³ TVL-TWA 1mg/m ³	REL-TWA 1mg/m ³ REL-TWA 0.1mg/m ³	PEL-TWA 0.1mg/m ³ PEL-TWA 1mg/m ³
7429-90-5	TVL-TWA 1mg/m ³	REL-TWA 2mg/m ³ REL-TWA 5mg/m ³ REL-TWA 10mg/m ³	PEL-TWA 5mg/m ³ PEL-TWA 15mg/m ³

Appropriate engineering controls: The usual precautionary measures for handling chemicals should be followed.

Remove all soiled and contaminated clothing immediately. Wash hands before breaks and at the end of work.

Personal Protective Equipment

Respiratory protection: Wear suitable protective mask in order to reduce the respiratory system. In case of leakage, wear chemical protective clothing, including self-contained breathing apparatus. **Hand protection:** Wear appropriate protective gloves to reduce skin contact.

Eyes protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and body protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and content of certain hazardous substances in the workplace.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties Color: Black Physical State: Prismatic **Odour:** Not available Odour Threshold: Not available **pH:** Not available Melting point/freezing point: Not available Initial boiling point and boiling range: Not available Flash Point: Not available Evaporation Rate: Not available Flammability (solid, gas): Not available Explosion Limits (vol% in air): Not available Vapour Pressure, kPa at 20°C: Not avialble Vapor Density: Not available Density/Relative Density (water=1): Not available Solubility(ies): Not available Partition Coefficient: n-octanal/water: Not available Auto-iginition Temperature: Not available **Decomposition Temperature:** Not available Viscosity: Not available Other Information: Not available Voltage: 12.8V Electric Capacity: 16000mAh Electric Energy: 204.8Wh



© 2017 Relion Battery, LLC. All rights reserved. Relion Battery is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Relion Battery reserves the right to make adjustments to this publication at any time, without notice or obligati

+1.803.547.7288 844.385.9840





SECTION 10 - STABILITY AND REACTIVITY

Reactivity: No data available Chemical Stability: Stable Possibility of Hazardous Reactions: No data available Conditions to Avoid: Flames, sparks and other sources of ignition, incompatible materials Incompatibilities Materials: Oxidizing agents, acid, base Hazardous Decomposition Products: Carbon monoxide, carbon

dioxide, lithium oxide fumes

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity:

CAS No.	LC50/LD50	
15365-14-7	No data available.	
1333-86-4	LD50 Rat (oral): 15400 mg/kg	
61789-96-6	No data available.	
24937-79-9	No data available. No data available.	
7782-42-5	No data available.	
7440-50-8	No data available.	
7429-90-5	No data available.	
1423-90-3	INU UALA AVAIIADIE.	

Skin Corrosion/Irritation: No data available Serious Eye Damage/Irritation: No data available Respiratory or Skin Sensitization: No data available Germ Cell Mutagenicity: No data available Carcinogenicity: No data available Reproductive Toxicity: No data available Specific Target Organ Toxicity-Single Exposure: No data available Specific Target Organ Toxicity-Repeated Exposure: No data available Aspiration Hazard: No data available Information on the Likely Routes of Exposure: No data available Eye: No data available Skin: No data available Ingestion: No data available

SECTION 12 - ECOLOGICAL INFORMATION

Ecological Toxicity: No data available Persistence and Degradability: No data available Bioaccumulative Potential: No data available Mobility in Soil: No data available Other Adverse Effects: No data available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Recommendation: Consult state, local or national regulations to ensure proper disposal. Uncleaned Packaging Recommendation: Disposal must be made according to official regulations.

SECTION 14 - TRANSPORT INFORMATION

Acute Toxicity:

UN Number IATA	
ΙΔΤΔ	
	UN3480
IMDG	UN3480
Model Regulation	UN3480
UN Proper shipping name	
IATA	Lithium ion batteries
IMDG	Lithium ion batteries
Model Regulation	Lithium ion batteries
Transport Hazard Class (es)	
IATA	9
IMDG	9
Model Regulation	9
Packing group	
IATA	N/A
IMDG	N/A
Model Regulation	N/A
Packing Sign IATA IMDG Model Regulation	
Environmental Hazards Marine Pollutant	No
Special precautions for user	



Inhalation: No data available

+1.803.547.7288 844.385.9840

© 2017 Relion Battery, LLC. All rights reserved. Relion Battery is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Relion Battery reserves the right to make adjustments to this publication at any time, without notice or obligatio

9868 Harrisburg Road Fort Mill, SC 29707, US





Transport Information:

RELION LIFePO4 Batteries have passed the test UN38.3, according to the Report ID: MLINHTU74733721.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according tot eh packaging Instruction 965 Section IA of IATA DGR 58th Edition for transportation, Cargo aircraft only.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the special provision 230, 348 of IMDG (37-14).

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the <<Recommendations On The Transport of Dangerous Goods-Model Regulations>> (19th).

Separate batteries to prevent short-circuiting and they should be packed in a strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames. Lithium ion cells and batteries must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.

Transport Fashion: By air, by sea, by railway, by road.

SECTION 15 - REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	LC50/LD50
15365-14-7	No data available.
1333-86-4	LD50 Rat (oral): 15400 mg/kg
61789-96-6	No data available.
24937-79-9	No data available.
7782-42-5	No data available.
21324-40-3	No data available.
7440-50-8	No data available.
7429-90-5	No data available.

SECTION 16 - OTHER INFORMATION

Issue Time: 2017-02-21

Issue Department: Technical Department Modification Record: Notice to Reader To the best of our knowledge, the information contained herein is accurate. However, neither the above names supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although., certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Other Information: CAS: (Chemical Abstracts Service) EC: (European Commission) ACGIH: (American Conference of Governmental Industrial Hygienists) NIOSH: (US National Institute for Occupational Safety and Health) **OSHA: (US Occupational Safety and Health)** TLV: (Threshold Limit Value) TWA: (Time Weighted Average) STEL: (Short Term Exposure Limit) PEL: (Permissible Exposure Average) **REL: (Recommended Exposure Limit)** PC-STEL: (Permissible concentration-time weighted average PC-TWA: (Permissible concentration-short time exposure limit) LC50: (Lethal concentration, 50 percent kill) LD50: Lethal dose, 50 percent kill) IARC: (International Agency for Research on Cancer) EC50: (Median effective concentration) BCF: (Bio concentration Factor) BOD: Biochemical Oxygen Demand) NOEC: (No observed effect concentration) NTP: (US National Toxicology Program) RTECS: (Registry of Toxic Effects of Chemical Substances) IATA: (International Air Transport Association) IMDG: (International Maritime Dangerous Goods) TDG: (Recommendations on the TRANSPORT OF DANGEROUS **GOODS Model Regulations**) TOC: (Total Organic Carbon) TSCA: (Toxic Substances Control Act of USA) DSL: 9The Domestic Substances List of Canada) NDSL: (The Non-Domestic Substances List of Canada)



© 2017 Relion Battery, LLC. All rights reserved. Relion Battery is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Relion Battery reserves the right to make adjustments to this publication at any time, without notice or obligation

+1.803.547.7288 844.385.9840 9868 Harrisburg Road Fort Mill, SC 29707, US

