

Auto | Marine | RV | Powersport | Lawn & Garden

NOCO BOOST[®]SPORT[®] JUMP STARTER



START DEAD BATTERIES.[™] Cars, Motorcycles, ATVs, Snowmobiles, Watercraft, Lawn & Garden.

UltraSafe, ultra-compact, rugged, and portable lithium-ion jump starter. Features spark-proof technology and reverse polarity protection. Instantly jump starts most single-battery applications, up to 20 times on a single charge. Ideal for powersport engines up to 4.0L Gas.



Safely connect to any 12-volt car battery with our mistake-proof design featuring spark-proof technology and reverse polarity protection.

JUMP START.

Full power to jump start a vehicle up to 20 times in one charge. Compatible with engines up to 4.0L gas.

USB CHARGE & RECHARGE.

It's internal battery can be used to recharge any personal mobile devices like smartphones, tablets, or any other USB device, and can be recharged by any powered USB port.

100 LUMENS.

The GB20 portable car battery jump starter integrates with a high-output 100 lumen LED flashlight with 7 light modes: low, medium, high, flashing, strobe, and emergency SOS.









A Fraction Of The Size.



4X Holds Charge Longer

The GB20 holds the charge four times longer to extend battery power life and eliminate charge time.

Compared to Leading Traditional Lead Acid Jump Starters

Powersport Precision Clamps with Integrated Eyelet Connectors

The narrow clamps easily reach terminals of powersport batteries and have detachable eyelets as an option when connecting to the battery.



(!)

Error LED. Illuminates Red if reverse polarity is detected.

Manual Override. Is a special feature designed for rare situations when a vehicle's battery is below 2-volts. Simply press and hold the manual overide button for 3 seconds, until the Boost LED starts flashing, to enter into the mode. Press the button again (Or the power button) to exit Manual Override. This mode should be used cautiously, as Manual Override disables safety protection while enabled.

Technical Specifications

Internal Battery:	24 Watt-Hour Lithium Ion	Housing Protection:	IP65 (w/ Ports closed)
Peak Current Rating:	500A	Cooling:	Natural Convection
Operating Temperature:	-4°F to +122°F (-20°C to +50°C)	Dimensions (LxWxH):	7.7 x 3.2 x 1.7 in
Charging Temperature:	32°F to +104°F (0°C to +40°C)	Unit Weight:	1.65 lbs
Storage Temperature:	-4°F to +122°F (-20°C to +50°C)	Unit Weight w/Clamps & Accessories:	2.1 lbs
Micro USB (Input):	5V, 2.1A		
USB (Output):	5V, 2.1A	LED Flashlight Brightness:	100 Lumens

Recharge Unit from any USB

Recharging a GB20 (for reference, results may vary)

USB Charger Rating	Charging Time	
.5A	12hr	
1A	6hr	
2A	3hr	

Retail Packaging:

Dimensions: 3.62"x4.57"x8.27" Weight: 2.69lbs UPC: 0-46221-15001-8

Inner Carton:

NOCO

Dimensions: 4.01"x8.78"x5.12" Weight: 2.87lbs

30339 Diamond Parkway, #102

Glenwillow, OH 44139 | USA 1.800.456.6626

Master Carton: Dimensions: 9.25"x12.60"x11.22" Weight: 18.08lbs Quantity: 6 UCC: 10046221150015

Units Per Pallet: NA - 360 Units EU - 270 Units

NO.CO

Microfiber Storage Bag
User Guide & Warranty Information
.22"
FC ROHS
Interest
Interest
Interest
Interest
Interest
Interest
Interest
Interest
Interest


What's In The Box

GB20 Lithium Jump Starter

Precision Battery Clamps

Micro USB Cable







NOCO[®] Patented Technology

or 12V port.

USB 2.1A Charge virtually any USB device, including Smartphones and Tablets.